

- FREEFORM PAL
- FREEFORM SV
- CONVENTIONAL PAL
- CONVENTIONAL SV

- EYEPOINT TECHNOLOGY®
- AS-WORN TECHNOLOGY™

NOTE:

- Recommended min fitting height is 16mm and 19 mm
- Prism to 10.00 Diopters

CR-39	TREATMENT						COATING
	Clear	Transitions®	Transitions® Signature7™	XTRActive	Vantage	Polarized	
POWER RANGE	-7.00 to +4.00	-7.00 to +4.00	-7.00 to +4.00	--	--	-7.00 to +4.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	--	--	+0.75 to +3.50	
CYLINDER	to -6.00	to -6.00	to -6.00	--	--	to -6.00	
OTHER		Gray/Brown	Gray/Brown	--	--	Gray/Brown/G-15	
INVISIBLE MARKINGS - 16mm	15 250 ES	TR 250 ES	TR 250 ES	--	--	PZ 250 ES	
INVISIBLE MARKINGS - 19mm	15 250 E	TR 250 E	TR 250 E	--	--	PZ 250 E	

SuperLite™ 1.74	TREATMENT					COATING
	Clear	Transitions®	Transitions® Signature7™	XTRActive	Polarized	
POWER RANGE	--					
ADD POWER	--					
CYLINDER	--					
OTHER	--					
INVISIBLE MARKINGS - 16mm	--					
INVISIBLE MARKINGS - 19mm	--					

SuperLite™ 1.60	TREATMENT						COATING
	Clear	Transitions®	Transitions® Signature7™	XTRActive	Vantage	Polarized	
POWER RANGE	-10.00 to +6.00	-10.00 to +6.00	-10.00 to +6.00	--	--	--	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	--	--	--	
CYLINDER	to -7.00	to -7.00	to -7.00	--	--	--	
OTHER		Gray/Brown	Gray/Brown	--	--	--	
INVISIBLE MARKINGS - 16mm	16 250 ES	T6 250 ES	T6 250 ES	--	--	--	
INVISIBLE MARKINGS - 19mm	16 250 E	T6 250 E	T6 250 E	--	--	--	

DLC™ TRIVEX™	TREATMENT					COATING
	Clear	Transitions®	Transitions® Signature7™	XTRActive	Polarized	
POWER RANGE	-13.25 to +6.00	-13.25 to +6.00	-13.25 to +6.00	-13.25 to +6.00	--	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	--	
CYLINDER	to -6.50	to -6.50	to -6.50	to -6.50	--	
OTHER		Gray/Brown	Gray/Brown	Gray	--	
INVISIBLE MARKINGS - 16mm	TX 250 ES	TTX 250 ES	TTX 250 ES	XX 250 ES	--	
INVISIBLE MARKINGS - 19mm	TX 250 E	TTX 250 E	TTX 250 E	XX 250 E	--	

SuperLite™ 1.67	TREATMENT					COATING
	Clear	Transitions®	XTRActive	Vantage	Polarized	
POWER RANGE	-12.50 to +8.00	-12.50 to +8.00	-12.50 to +8.00	--	--	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	--	--	
CYLINDER	to -8.00	to -8.00	to -8.00	--	--	
OTHER		Gray/Brown	Gray	--	--	
INVISIBLE MARKINGS - 16mm	67 250 ES	T67 250 ES	X67 250 ES	--	--	
INVISIBLE MARKINGS - 19mm	67 250 E	T67 250 E	X67 250 E	--	--	

POLYPLUS™/ POLYCARBONATE	TREATMENT						COATING
	Clear	Transitions®	Transitions® Signature7™	XTRActive	Vantage	Polarized	
POWER RANGE	-10.00 to +6.00	-10.00 to +6.00	-10.00 to +6.00	--	--	-10.00 to +6.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	--	--	+0.75 to +3.50	
CYLINDER	to -7.00	to -7.00	to -7.00	--	--	to -7.00	
OTHER		Gray/Brown	Gray/Brown	--	--	Gray/Brown/G-15	
INVISIBLE MARKINGS - 16mm	PC 250 ES	PT 250 ES	PT 250 ES	--	--	PPZ 250 ES	
INVISIBLE MARKINGS - 19mm	PC 250 E	PT 250 E	PT 250 E	--	--	PPZ 250 E	

- Crizal AR Coating
- Hoya AR Coating
- Zeiss AR Coating
- iCoat AR Coating

- Denotes that material is available in a Shamir Freeform Blank™

All Shamir products are available with your lab's in-house AR Coatings. Please check with your lab to determine which specific manufacturer's AR coating is available with the Shamir lens and material that you are ordering, as a manufacturer may offer more than one AR coating.

EFFECTIVE DATE: NOV. 18, 2013