

- FREEFORM PAL
- FREEFORM SV
- CONVENTIONAL PAL
- CONVENTIONAL SV

- EYEPOINT TECHNOLOGY®
- AS-WORN TECHNOLOGY™

NOTE:

- Recommended min fitting heights are 15mm and 18mm
- Prism to 4.00 Diopters

CR-39	TREATMENT					COATING
	Clear	Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	
CYLINDER	to -6.00	to -6.00	to -6.00	to -6.00	to -6.00	
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS - 15mm	15 250 I15	TR 250 I15	X5 250 I15	V5 250 I15	PZ 250 I15	
INVISIBLE MARKINGS - 18mm	15 250 I18	TR 250 I18	X5 250 I18	V5 250 I18	PZ 250 I18	

SuperLite™ 1.74	TREATMENT		COATING
	Clear		
POWER RANGE	-18.75 to +15.50		
ADD POWER	+0.75 to +3.50		
CYLINDER	to -9.00		
OTHER			
INVISIBLE MARKINGS - 15mm	74 250 I15		
INVISIBLE MARKINGS - 18mm	74 250 I18		

SuperLite™ 1.60	TREATMENT					COATING
	Clear	Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE	-15.00 to +6.00	-15.00 to +6.00	-15.00 to +6.00	--	-15.00 to +6.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	--	+0.75 to +3.50	
CYLINDER	to -7.00	to -7.00	to -7.00	--	to -7.00	
OTHER		Gray/Brown	Gray	--	Gray/Brown	
INVISIBLE MARKINGS - 15mm	16 250 I15	T6 250 I15	X6 250 I15	--	PZ6 250 I15	
INVISIBLE MARKINGS - 18mm	16 250 I18	T6 250 I18	X6 250 I18	--	PZ6 250 I18	

DLC™ TRIVEX™	TREATMENT				COATING
	Clear	Transiti@ns	XTRActive	Polarized	
POWER RANGE	-13.25 to +6.00	-13.25 to +6.00	-13.25 to +6.00	-13.25 to +6.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	
CYLINDER	to -6.50	to -6.50	to -6.50	to -6.50	
OTHER		Gray/Brown	Gray	Gray/Brown	
INVISIBLE MARKINGS - 15mm	TX 250 I15	TTX 250 I15	XX 250 I15	PTX 250 I15	
INVISIBLE MARKINGS - 18mm	TX 250 I18	TTX 250 I18	XX 250 I18	PTX 250 I18	

SuperLite™ 1.67	TREATMENT					COATING
	Clear	Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE	-16.00 to +8.00	-16.00 to +8.00	-16.00 to +8.00	--	-16.00 to +8.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	--	+0.75 to +3.50	
CYLINDER	to -8.00	to -8.00	to -8.00	--	to -8.00	
OTHER		Gray/Brown	Gray	--	Gray/Brown	
INVISIBLE MARKINGS - 15mm	67 250 I15	T67 250 I15	X67 250 I15	--	PZ67 250 I15	
INVISIBLE MARKINGS - 18mm	67 250 I18	T67 250 I18	X67 250 I18	--	PZ67 250 I18	

POLYPLUS™/ POLYCARBONATE	TREATMENT					COATING
	Clear	Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE	-14.75 to +6.00	-14.75 to +6.00	-14.75 to +6.00	-14.75 to +6.00	-14.75 to +6.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	
CYLINDER	to -7.00	to -7.00	to -7.00	to -7.00	to -7.00	
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS - 15mm	PC 250 I15	PT 250 I15	PX 250 I15	PV 250 I15	PPZ 250 I15	
INVISIBLE MARKINGS - 18mm	PC 250 I18	PT 250 I18	PX 250 I18	PV 250 I18	PPZ 250 I18	

- Crizal AR Coating
- Hoya AR Coating
- Zeiss AR Coating
- iCoat AR Coating

All Shamir products are available with your lab's in-house AR Coatings. Please check with your lab to determine which specific manufacturer's AR coating is available with the Shamir lens and material that you are ordering, as a manufacturer may offer more than one AR coating.

EFFECTIVE DATE: APR. 8, 2013

- Denotes that material is available in a Shamir Freeform Blank™